

### **Listing of Claims**

1           Claim 1 (Currently Amended): A method of enabling an operator to remotely  
2 manage a plurality of field devices designed to implement a process in a plant, said plant  
3 further containing a field device management station (FDMS) coupled to said plurality  
4 of field devices by a control network, wherein said FDMS is designed to issue a plurality  
5 of commands to each of said plurality of field devices on said control network, said  
6 method comprising:

7           providing a wireless connection from a first client, wherein said wireless  
8 connection provides communication between said first client and said FDMS, wherein  
9 said wireless connection is provided to cover the entire communication path between said  
10 FDMS and said first client;

11           enabling said operator to issue a first command from said first client to a first field  
12 device contained in said plurality of field devices, wherein said first command is  
13 contained in said plurality of commands;

14           transferring an indication from said first client to said FDMS on said wireless  
15 connection in response to said first command being issued by said operator, said  
16 indication indicating that said operator has issued said first command from said first  
17 client;

18           forwarding said first command from said FDMS to said first field device on said  
19 control network in response to receiving said indication,

20           whereby said operator manages said plurality of field devices using said first client  
21 based on said wireless connection,

22           providing a wire-based connection between a second client and said FDMS;

23           enabling said operator to issue an another command from said second client, said  
24 another command being directed to a second field device contained in said plurality of  
25 field devices;

26           transferring an another indication from said second client to said FDMS on said  
27 wire-based connection upon said operator user issuing said another command; and

28           forwarding said another command from said FDMS to said second field device on

29 said control network upon receiving said another indication,  
30 whereby commands from said first client and said second client are channeled  
31 through said FDMS.

1 Claim 2 (Currently Amended): A method of enabling an operator to remotely  
2 manage a plurality of field devices designed to implement a process in a plant, said plant  
3 further containing a field device management station (FDMS) coupled to said plurality  
4 of field devices by a control network, wherein said FDMS is designed to issue a plurality  
5 of commands to each of said plurality of field devices on said control network, said  
6 method comprising:

7 providing a wireless connection from a first client, wherein said wireless  
8 connection provides communication between said first client and said FDMS;

9 enabling said operator to issue a first command from said first client to a first field  
10 device contained in said plurality of field devices, wherein said first command is  
11 contained in said plurality of commands;

12 transferring an indication from said first client to said FDMS on said wireless  
13 connection in response to said first command being issued by said operator, said  
14 indication indicating that said operator has issued said first command from said first  
15 client;

16 forwarding said first command from said FDMS to said first field device on said  
17 control network in response to receiving said indication,

18 whereby said operator manages said plurality of field devices using said first client  
19 based on said wireless connection,

20 providing a wire-based connection between a second client and said FDMS;

21 enabling said operator to issue an another command from said second client, said  
22 another command being directed to a second field device contained in said plurality of  
23 field devices;

24 transferring an another indication from said second client to said FDMS on said  
25 wire-based connection medium upon said operator ~~user~~ issuing said another command;

26 forwarding said another command from said FDMS to said second field device on  
27 said control network upon receiving said another indication,  
28 whereby commands from said first client and said second client are channeled  
29 through said FDMS;  
30 connecting said first client to said second field device contained in said plurality  
31 of field devices;  
32 transferring a second command from said FDMS to said first client using said  
33 wireless connection, wherein said second command is directed to said second field  
34 device; and  
35 sending said second command from said first client to said second field device,  
36 whereby said second command is forwarded from said FDMS to said second field device  
37 without using said control network.

1 **Claim 3 (Previously Presented):** The method of claim 2, further comprising  
2 enabling said operator to issue said second command from said first client, wherein said  
3 FDMS receives a second indication from said first client, said second indication  
4 indicating that said second command has been issued at said first client and performs said  
5 **forwarding** said second command upon receiving said second indication.

1 **Claim 4 (Previously Presented):** The method of claim 2, wherein said wireless  
2 connection is provided to cover the entire communication path between said FDMS and  
3 said first client.

1 **Claim 5 (Previously Presented):** The method of claim 2, wherein said wireless  
2 connection is provided between said first client and a network device, wherein said  
3 network device is connected to a network connecting said network device to said FDMS  
4 by a wire-based medium.

1 **Claim 6 (Canceled)**

1           Claim 7 (Previously Presented): The method of claim 2, further comprising  
2 maintaining a central log of said first command, said second command and said another  
3 command in said FDMS, wherein said central log is updated after said operator issues  
4 said first command, said second command and said another command respectively.

1           Claim 8 (Currently Amended): A field device management station (FDMS)  
2 enabling management of a plurality of field devices, said plurality of field devices being  
3 coupled to said FDMS by a control network, said FDMS comprising:

4           a wireless interface providing connectivity to a first client by a wireless medium;  
5 and

6           a data manager block receiving an indication from said first client on said wireless  
7 medium, said indication indicating that a first command has been issued from said first  
8 client, said first command being directed to a first field device contained in said plurality  
9 of field devices, said data manager block forwarding said first command on said control  
10 network in response to receiving said indication,

11           wherein said first command is issued by an operator from said first client such that  
12 said operator manages said plurality of field devices using said first client from locations  
13 distant from said FDMS,

14           a wire-line interface providing connectivity to a second client by a wire-line based  
15 medium,

16           said data manager block receiving another indication from said second client by  
17 said wire-line based medium, said another indication indicating that a second command  
18 directed to a second field device contained in said plurality of devices has been issued,  
19 said data manager block forwarding said second command to said second field device on  
20 said control network in response to receiving said another indication.

1           Claim 9 (Currently Amended): A field device management station (FDMS)  
2 enabling management of a plurality of field devices, said plurality of field devices being

3 coupled to said FDMS by a control network, said FDMS comprising:

4 a wireless interface providing connectivity to a first client by a wireless medium;  
5 and

6 a data manager block receiving an indication from said first client on said wireless  
7 medium, said indication indicating that a first command has been issued from said first  
8 client, said first command being directed to a first field device contained in said plurality  
9 of field devices, said data manager block forwarding said first command on said control  
10 network in response to receiving said indication,

11 wherein said first command is issued by an operator from said first client such that  
12 said operator manages said plurality of field devices using said first client from locations  
13 distant from said FDMS,

14 a wire-line interface providing connectivity to a second client by a wire-line based  
15 medium,

16 said data manager block receiving another indication from said second client by  
17 said wire-line based medium, said another indication indicating that a second command  
18 directed to a second field device contained in said plurality of devices has been issued,  
19 said data manager block forwarding said second command to said second field device on  
20 said control network in response to receiving said another indication,

21 wherein said data manager block is operable to receive a third indication from said  
22 first client on said wireless medium, said third indication indicating that a third command  
23 directed to a third field device contained in said plurality of field devices has been issued  
24 from said first client, said third field device being connected to said first client, said data  
25 manager block forwarding said third command on said wireless medium to said first client  
26 in response to receiving said third indication.

1 Claim 10 (Canceled)

1 **Claim 11 (Currently Amended):** The FDMS of claim 9, further comprising:

2 a wireless client handler provided between said wireless interface and said data

3 manager block, said wireless client handler receiving said first indication on said wireless  
4 medium, said wireless client handler further receiving a first response from said data  
5 manager block and forwarding said first response on said wireless medium to said first  
6 client; and

7 a wire-line client handler provided between said wire-line interface and said data  
8 manager block, said ~~wire-based~~ wire-line client handler receiving said second **indication**  
9 on said ~~wire-based~~ wire-line based medium, said ~~wire-based~~ wire-line client handler  
10 further receiving a second response from said data manager block and forwarding said  
11 second response on said ~~wire-based~~ wire-line based medium.

1 Claim 12 (Currently Amended): The FDMS of claim 11, wherein said data  
2 manager block receives a request to establish a connection from said first client and  
3 instantiates said wireless client handler in response to receiving said request.

1 Claim 13 (Currently Amended): The FDMS of claim 9, wherein said data manager  
2 block maintains a central log containing information on said first command and said  
3 second command.

1 Claim 14 (Previously Presented): A computer readable medium carrying one or  
2 more sequences of instructions for causing a field device management station (FDMS)  
3 to enable management of a plurality of field devices, said plurality of field devices being  
4 coupled to said FDMS by a control network, wherein execution of said one or more  
5 sequences of instructions by one or more processors contained in said FDMS causes said  
6 one or more processors to perform the actions of:

7 receiving a first indication from a first client on a wireless medium, said first  
8 indication indicating that a first command directed to a first field device contained in said  
9 plurality of field devices has been issued from said first client;

10 forwarding said first command on said control network to said first field device in  
11 response to receiving said first indication,

12 wherein said first command is issued by an operator from said first client such that  
13 said operator manages said plurality of field devices using said first client,  
14 receiving a third indication from a third client on a wire-line based medium, said  
15 third indication indicating that a third command directed to a third field device contained  
16 in said plurality of devices has been issued from said third client; and  
17 forwarding said third command to said third field device on said control network in  
18 response to receiving said third indication.

1 Claim 15 (Previously Presented): A computer readable medium carrying one or  
2 more sequences of instructions for causing a field device management station (FDMS)  
3 to enable management of a plurality of field devices, said plurality of field devices being  
4 coupled to said FDMS by a control network, wherein execution of said one or more  
5 sequences of instructions by one or more processors contained in said FDMS causes said  
6 one or more processors to perform the actions of:

7 receiving a first indication from a first client on a wireless medium, said first  
8 indication indicating that a first command directed to a first field device contained in said  
9 plurality of field devices has been issued from said first client;

10 forwarding said first command on said control network to said first field device in  
11 response to receiving said first indication,

12 wherein said first command is issued by an operator from said first client such that  
13 said operator manages said plurality of field devices using said first client,

14 receiving a third indication from a third client on a wire-line based medium, said  
15 third indication indicating that a third command directed to a third field device contained  
16 in said plurality of devices has been issued from said third client;

17 forwarding said third command to said third field device on said control network in  
18 response to receiving said third indication;

19 receiving a second indication from said first client on said wireless medium, said  
20 second indication indicating that a second command directed to a second field device  
21 contained in said plurality of field devices has been issued from said first client, said

22 second field device being connected to said first client; and  
23 forwarding said second command on said wireless medium to said first client in  
24 response to receiving said indication.

Claim 16 (Canceled)

1 Claim 17 (Previously Presented): The computer readable medium of claim 15,  
2 further comprising maintaining a central log containing information on said first  
3 command, third command and said second command.

1 Claim 18 (Currently Amended): A computer readable medium carrying one or  
2 more sequences of instructions for causing a client to enable remote management of a  
3 plurality of field devices, said plurality of field devices being coupled to a field device  
4 management station (FDMS) by a control network, wherein execution of said one or more  
5 sequences of instructions by one or more processors contained in said client causes said  
6 one or more processors to perform the actions of:

7 enabling ~~a user~~ an operator to issue a first command directed to a first field device  
8 contained in said plurality of field devices;

9 sending an indication to said FDMS on a wireless medium, said first indication  
10 indicating that said command directed to said first field device has been issued;

11 receiving a first response on said wireless medium from said FDMS;

12 wherein said operator manages said plurality of field devices using said client,

13 wherein said client is connected to a second field device by a path,

14 enabling said operator ~~user~~ to issue a second command from said client, wherein  
15 said second command is directed to said second field device contained in said plurality  
16 of field devices;

17 sending a second indication to said FDMS on said wireless medium indicating that  
18 said second command directed to said second field has been issued;

19 receiving said second command from said FDMS on said wireless medium; and



20 forwarding said second command to said second field device on said path after  
21 said receiving from said FDMS.

1 Claim 19 (Canceled)

1 **Claim 20 (Previously Presented):** A method of enabling an operator to remotely  
2 manage a plurality of field devices designed to implement a process in a plant, said plant  
3 further containing a field device management station (FDMS) coupled to said plurality  
4 of field devices by a control network, said method comprising:

5 providing a wireless connection from a first client, wherein said wireless  
6 connection provides communication between said first client and said FDMS;

7 enabling said operator to issue a first command from said first client to a first field  
8 device contained in said plurality of field devices;

9 transferring said first command from said first client to said FDMS on said  
10 wireless connection;

11 forwarding said first command from said FDMS to said first field device on said  
12 control network,

13 whereby said operator manages said plurality of field devices using said first client,

14 connecting said first client to a second field device contained in said plurality of  
15 field devices;

16 transferring a second command from said FDMS to said first client using said  
17 wireless connection, wherein said second command is directed to said second field  
18 device;

19 sending said second command from said first client to said second field device,  
20 whereby said second command is forwarded from said FDMS to said second field device  
21 without using said control network; and

22 enabling said operator to issue said second command from said first client, wherein  
23 said FDMS receives said second command and performs said forwarding said second  
24 command.

1 Claim 21 (Canceled)

1 Claim 22 (Currently Amended): ~~The method of claim 1, further comprising~~ A  
2 method of enabling an operator to remotely manage a plurality of field devices designed  
3 to implement a process in a plant, said plant further containing a field device management  
4 station (FDMS) coupled to said plurality of field devices by a control network, wherein  
5 said FDMS is designed to issue a plurality of commands to each of said plurality of field  
6 devices on said control network, said method comprising:

7 \_\_\_\_\_ providing a wireless connection from a first client, wherein said wireless  
8 connection provides communication between said first client and said FDMS;

9 \_\_\_\_\_ enabling said operator to issue a first command from said first client to a first field  
10 device contained in said plurality of field devices, wherein said first command is  
11 contained in said plurality of commands;

12 \_\_\_\_\_ transferring an indication from said first client to said FDMS on said wireless  
13 connection in response to said first command being issued by said operator, said  
14 indication indicating that said operator has issued said first command from said first  
15 client;

16 \_\_\_\_\_ forwarding said first command from said FDMS to said first field device on said  
17 control network in response to receiving said indication,

18 \_\_\_\_\_ whereby said operator manages said plurality of field devices using said first client  
19 based on said wireless connection,

20 \_\_\_\_\_ providing a wire-based connection between a second client and said FDMS;

21 \_\_\_\_\_ enabling said operator to issue an another command from said second client, said  
22 another command being directed to a second field device contained in said plurality of  
23 field devices;

24 \_\_\_\_\_ transferring an another indication from said second client to said FDMS on said  
25 wire-based connection upon said operator issuing said another command; and

26 \_\_\_\_\_ forwarding said another command from said FDMS to said second field device on

27 said control network upon receiving said another indication,

28 whereby commands from said first client and said second client are channeled  
29 through said FDMS; and

30 maintaining a central log of said first command and said another command in said  
31 FDMS, wherein said central log is updated after said operator issues said first command  
32 and said another command respectively.

1 Claim 23 (Previously Presented): The FDMS of claim 9, further comprising a  
2 database interface maintaining a central log of said first command and said another  
3 command, wherein said central log is updated after said operator issues said first  
4 command and said another command respectively.

1 Claim 24 (Previously Presented) : The method of claim 20, wherein said wireless  
2 connection is provided to cover the entire communication path between said FDMS and  
3 said first client.